Wireless Pro 2Ch Standard





Discover the Wireless Stimulation

WIRELESS PRO 2 CH STANDARD is a wireless 2 channel stimulator developed for Physiotherapists and Rehab Clinics that require a standard wireless option for electro stimulation. Delivered with 2 modules, 1 remote and a basic docking station, it meets all of the requirements a professional demands; pain management, treatment of vascular diseases, and muscle stimulation with basic programs.

Features

Programs

4 standard program categories: Rehabilitation I, Pain I, Vascular and Conditioning I. Standard program configuration - 2CH.

Wireless Technology

Remove constraints for you and your patient. Gives your patient a total freedom of movement facilitating patient manipulations and allowing you to combine active exercise with electro stimulation for a better result.

Muscle Intelligence™ Tecnhology

4 functions Mi-Scan, Mi-Tens, Mi-Range and Mi-Action are available on each module (2 modules delivered).

Remote Control

Design adapted to professional use with a silicon keypad that acts as a safeguard against water and gel penetration, and offers better ergonomic conditions in terms of keyboard use and buttons.

+ TENS Option

Select one program and add TENS on other channels. This allows treatment of two different body parts, two patients at the same time or combines TENS and NMES when this kind of stimulation is required.

Skip

Manage the session time and move directly in the next phase (recovery) when needed.

Autonomy and Speed Recharge

Daily use autonomy with the charger included in the kit, a full cycle of recharging will take a maximum of 2.5 hours.

Software

Create your patient and history list and create customized stimulation programs.

Warranty

The warranty is for 3 years from the date of purchase.

Waveforms	
7	 Symmetrical Biphasic 100% compensated

Ordering Information	
Description	
Wireless Pro 2 Ch Standard	
WPRO STD2CH-LP1 EN-FR-SP-IT-DE- NL-PT-TU-CZ Plug EU	
WPRO STD2CH-LP1 EN-FR-SP-IT-DE- NL-PT-TU-CZ Plug EU UK US AUS	
WPRO STD2CH- LP3 EN-DA-SV-NO- FI-RU Plug EU	

Standard Accessories	
0013X	Remote control (x1) std
984350	Stimulation modules (x2)
101091	Basic 2 ch docking station
108X	AC adaptor
601163	USB cable
46262XX	User manual and practical guide on CD/USB
885932	Quick start guide/warning leaflet
602047	Bottle of gel
980020	Motor point pen
680085	Transportation pouch
1494	Lanyard
5529024	White protection sleeve
5529220	Set of colored module clips

Technical Specific	ations
Channels:	4
Constant current:	Up to a resistance of Max 1300 Ohm/channel
Maximum pulse intensity:	120 mA.
Pulse intensity increments:	0.25 mA.
Pulse width:	30μs to 1000ms
Pulse frequency:	1 to 150 Hz.
MDD:	Class IIa
IP class:	IP22
Applied part:	Type BF Comply with safety tests: IEC 60601-1, IEC 60601-1-2, IEC 60601-2-10
Power supplies:	Lithium polymer (LiPo) rechargeable $3.7[V] / \ge 1500[mAh]$.
Dimensions:	Remote control: 105 x 66 x 19 mm
Module:	55 x 16 mm
Docking station:	188 x 134 x 80 mm
Weight: Remote control:	116 g incl. battery
Module:	62 g incl. battery
Docking station 2CH:	250g